Modul:Format link/Doku

Dies ist die Dokumentationsseite für Modul:Format link

This module, migrated from origins in Module:Hatnote, provides functionality for formatting links for display, including that powering the Vorlage:Tl template.

It can pretty-format section links with the section symbol ("§") and appropriate whitespace, it automatically escapes category and file names with the colon trick, and includes functionality for italicizing the page or section name, and for detecting and categorizing results that produce red links.

Inhaltsverzeichnis

1 Use from wikitext 1
2 Use from other Lua modules 1
2.1 _formatLink 1
2.2 formatPages 2
3 Errors 3

Use from wikitext

The functions in this module cannot be used directly from #invoke, and must be used through templates instead. Please see Template:Format link for documentation on usage of that template.

Use from other Lua modules

To load this module from another Lua module, use the following code:

```
local mFormatLink = require('Module:Format link')
```

You can then use the functions as documented below.

_formatLink

```
mFormatLink._formatLink{
    link = 'Link',
    display = 'Display',
    target = 'Target',
    italicizePage = true,
    italicizeSection = true,
    categorizeMissing = 'Pages using formatted red links'
}
```

Formats *link* as a wikilink. Categories and files are automatically escaped with the colon trick, and links to sections are automatically formatted as *page § section*, rather than the MediaWiki default of *page#section*.

Several options modify the output:

- If the *display* value is present, then it will be used as a display value. Any manual piping (using the {{!}} magic word or similar) present in *link* will be overridden by the *display* value if present.
- If the *target* value is present, then it will override *link* as a target, but the result will still be *displayed* using either the value from *display*, or the result of formatting *link*.
- If *italicizePage* is true, then the page portion of the link is italicized if present.
- If *italicizeSection* is true, then the section portion of the link is italicized if present.
- If *categorizeMissing* is a non-empty string, then that value is used as a category name, and that category will be applied if the resulting target of the link (no matter whether through *link* or through *target*) doesn't exist.

Examples

`mFormatLink._formatLink{link = 'Foo#Bar'}` → [[:Foo#Bar|Foo § Bar]] → Vorlage:Format link

`mFormatLink._formatLink{link = 'Baz', display = 'Qux'}` → [[:Baz|Qux]] → Vorlage:Format link

`mFormatLink._formatLink{link = 'Foo|Bar', display = 'Baz'}` → [[:Foo|Baz]] → Vorlage:Format link

`mFormatLink._formatLink{link = '#Foo', target = 'Example#Foo'}` → [[:Example#Foo|§ Foo]] → Vorlage:Format link

`mFormatLink._formatLink{link = 'The Lord of the Rings#Plot', italicizePage = true}` → [[:The Lord of the Rings#Plot|''The Lord of the Rings'' § Plot]] → Vorlage:Format link

`mFormatLink._formatLink{link = 'Cybercrime Prevention Act of 2012#Disini v. Secretary of Justice', italicizeSection = true}` → [[:Cybercrime Prevention Act of 2012#Disini v. Secretary of Justice|Cybercrime Prevention Act of 2012 § ''Disini v. Secretary of Justice'']] → Vorlage:Format link

`mFormatLink._formatLink{link = 'Nonexistent page', categorizeMissing = 'Example'}` → [[:Nonexistent page]][[Category:Example]] → Vorlage:Format link

`mFormatLink._formatLink{link = 'Existing', categorizeMissing = 'Example'}` → [[:Existing]] → Vorlage:Format link

formatPages

```
mFormatLink.formatPages(options, pages)
```

This derived function is useful for lists that format many links. It formats an array of pages using the _formatLink function, and returns the result as an array. Options in the *options* table are applied, and use the same names as the options for *_formatLink*.

Example

Vorlage:Code → Vorlage:Code

Errors

If *_formatLink* is used and neither a *link* nor a *target* argument is provided, then the module will produce an error message instead of its usual output, as it *cannot* then produce valid output.

You can solve this error by providing appropriate parameters to *_formatLink*, or you may want to ensure that a more descriptive error is provided by a downstream template or module when it would otherwise call *_formatLink* with inadequate arguments.