



# Inhaltsverzeichnis

---

# Modul:Demo/Doku

---

Dies ist die Dokumentationsseite für **Modul:Demo**

## Inhaltsverzeichnis

1 Usage .....	2
1.1 Usage via templates .....	2
1.2 Usage in a module .....	2
2 See also .....	3

## Usage

---

### Usage via templates

---

This module supports **Vorlage:T**

```
{{#invoke:Demo|main}}
```

and **Vorlage:T**

```
{{#invoke:Demo|inline}}
```

The input must be wrapped in **Vorlage:Tag** tags or else it may be processed before the module can read it.

### Usage in a module

---

If you want to use this in another module (such as to make the output prettier), you can get values like so:

```
require('Module:demo').get(frame)
```

Function `get()` returns a table containing:

- `source` = the source code (without **Vorlage:Tag** wrappers, characters substituted with html entities)
- `output` = the execution result of the source.
- `frame` = the frame from which this template took the parameter.

By default, `get()` takes the first parameter of frame. If the frame uses a different parameter name for the nowiki-wrapped source, then place that name (as a string) as the second parameter, like so `require('Module:demo').get(frame, 'alternate_name')`



### Example:

```
p = {}  
  
function p.main(frame)  
  local parts = require('Module:demo').get(frame)  
  return '<Pretty html><pre>' .. parts.source .. '</pre><more pretty html>' .. pa  
end  
  
return p
```

### See also

---

- [Template:Nowiki template demo](#) which uses [Module:Template test case](#)
- [Template:Automarkup](#) which uses [Module:Automarkup](#)