Inhaltsverzeichnis

1. Modul:DemoTemplate/Doku 2
2. Modul:DemoTemplate 3

Modul:DemoTemplate/Doku

Dies ist die Dokumentationsseite für Modul:DemoTemplate

Usage

Simply place "#invoke:DemoTemplate|" before a call to a template. For example, {{#invoke:DemoTemplate|Convert|10|km|nmi|abbr=off}} yields the following:

`{{Convert|10|km|nmi|abbr=off}}` → Vorlage:Convert

This module handles both named and positional parameters as well as equals signs in both parameter names and values correctly, so this (for example) will work: {{#invoke:DemoTemplate|1x|1=Some parameter with an = sign in it}}

`{{1x|1=Some parameter with an = sign in it}}` → Vorlage:1x

Note, however, that pipes, curly braces, etc. are not currently handled correctly by this module, so this (for example) will **not** work correctly: {{#invoke:DemoTemplate|1x|foo{{!}}bar}}

`{{1x|foo|bar}}` → Vorlage:1x

Modul:DemoTemplate

Usage

Simply place "#invoke:DemoTemplate|" before a call to a template. For example, {{#invoke:DemoTemplate|Convert|10|km|nmi|abbr=off}} yields the following:

`{{Convert|10|km|nmi|abbr=off}}` → Vorlage:Convert

This module handles both named and positional parameters as well as equals signs in both parameter names and values correctly, so this (for example) will work: {{#invoke:DemoTemplate|1x|1=Some parameter with an = sign in it}}

`{{1x|1=Some parameter with an = sign in it}}` → Vorlage:1x

Note, however, that pipes, curly braces, etc. are not currently handled correctly by this module, so this (for example) will **not** work correctly: {{#invoke:DemoTemplate|1x|foo{{!}}bar}}

`{{1x|foo|bar}}` → Vorlage:1x

```
require('Module:No globals')

local newBuffer = require('Module:OutputBuffer')
local mt = {}

function mt.__index(t, title)
        return function(frame)
                local getBuffer, print, printf = newBuffer()
                printf('{{%s', title)
                local ipairsArgs = {}
                for k,v in ipairs(frame.args) do
                        if string.find(v, '=', 1, true) then
                                break
                        end
                        ipairsArgs[k] = true
                        printf('|%s', v)
                end
                for k,v in pairs(frame.args) do
                        if not ipairsArgs[k] then
                                printf('|%s=%s', string.gsub(k, '=', '{{=}}'), v)
                        end
                end
                print('}}')
                local buffer = getBuffer()
                -- rather than calling expandTemplate with the title and args we
                return string.format('<code>%s</code> &rarr; %s', mw.text.nowiki(
        end
end

return setmetatable({}, mt)
```