Inhaltsverzeichnis

1. Modul:Format link 2
2. Modul:Format link/Doku 8

Modul:Format link

This module, migrated from origins in Module:Hatnote, provides functionality for formatting links for display, including that powering the Vorlage:Tl template.

It can pretty-format section links with the section symbol ("§") and appropriate whitespace, it automatically escapes category and file names with the colon trick, and includes functionality for italicizing the page or section name, and for detecting and categorizing results that produce red links.

Inhaltsverzeichnis

1 Use from wikitext 2
2 Use from other Lua modules 2
2.1 _formatLink 2
2.2 formatPages 3
3 Errors 4

Use from wikitext

The functions in this module cannot be used directly from #invoke, and must be used through templates instead. Please see Template:Format link for documentation on usage of that template.

Use from other Lua modules

To load this module from another Lua module, use the following code:

```
local mFormatLink = require('Module:Format link')
```

You can then use the functions as documented below.

_formatLink

```
mFormatLink._formatLink{
    link = 'Link',
    display = 'Display',
    target = 'Target',
    italicizePage = true,
    italicizeSection = true,
    categorizeMissing = 'Pages using formatted red links'
}
```

Formats *link* as a wikilink. Categories and files are automatically escaped with the colon trick, and links to sections are automatically formatted as *page § section*, rather than the MediaWiki default of *page#section*.

Several options modify the output:

- If the *display* value is present, then it will be used as a display value. Any manual piping (using the `{{!}}` magic word or similar) present in *link* will be overridden by the *display* value if present.
- If the *target* value is present, then it will override *link* as a target, but the result will still be *displayed* using either the value from *display*, or the result of formatting *link*.
- If *italicizePage* is true, then the page portion of the link is italicized if present.
- If *italicizeSection* is true, then the section portion of the link is italicized if present.
- If *categorizeMissing* is a non-empty string, then that value is used as a category name, and that category will be applied if the resulting target of the link (no matter whether through *link* or through *target*) doesn't exist.

Examples

`mFormatLink._formatLink{link = 'Foo#Bar'}` → [[:Foo#Bar|Foo § Bar]] → Vorlage:Format link

`mFormatLink._formatLink{link = 'Baz', display = 'Qux'}` → [[:Baz|Qux]] → Vorlage:Format link

`mFormatLink._formatLink{link = 'Foo|Bar', display = 'Baz'}` → [[:Foo|Baz]] → Vorlage:Format link

`mFormatLink._formatLink{link = '#Foo', target = 'Example#Foo'}` → [[:Example#Foo|§ Foo]] → Vorlage:Format link

`mFormatLink._formatLink{link = 'The Lord of the Rings#Plot', italicizePage = true}` → [[:The Lord of the Rings#Plot|''The Lord of the Rings'' § Plot]] → Vorlage:Format link

`mFormatLink._formatLink{link = 'Cybercrime Prevention Act of 2012#Disini v. Secretary of Justice', italicizeSection = true}` → [[:Cybercrime Prevention Act of 2012#Disini v. Secretary of Justice|Cybercrime Prevention Act of 2012 § ''Disini v. Secretary of Justice'']] → Vorlage:Format link

`mFormatLink._formatLink{link = 'Nonexistent page', categorizeMissing = 'Example'}` → [[:Nonexistent page]][[Category:Example]] → Vorlage:Format link

`mFormatLink._formatLink{link = 'Existing', categorizeMissing = 'Example'}` → [[:Existing]] → Vorlage:Format link

formatPages

```
mFormatLink.formatPages(options, pages)
```

This derived function is useful for lists that format many links. It formats an array of pages using the _formatLink function, and returns the result as an array. Options in the *options* table are applied, and use the same names as the options for *_formatLink*.

Example

Vorlage:Code → Vorlage:Code

Errors

If *_formatLink* is used and neither a *link* nor a *target* argument is provided, then the module will produce an error message instead of its usual output, as it *cannot* then produce valid output.

You can solve this error by providing appropriate parameters to *_formatLink*, or you may want to ensure that a more descriptive error is provided by a downstream template or module when it would otherwise call *_formatLink* with inadequate arguments.

```
--------------------------------------------------------------------------------
-- Format link
--
-- Makes a wikilink from the given link and display values. Links are escaped
-- with colons if necessary, and links to sections are detected and displayed
-- with " § " as a separator rather than the standard MediaWiki "#". Used in
-- the {{format link}} template.
--------------------------------------------------------------------------------
local libraryUtil = require('libraryUtil')
local checkType = libraryUtil.checkType
local checkTypeForNamedArg = libraryUtil.checkTypeForNamedArg
local mArguments -- lazily initialise [[Module:Arguments]]
local mError -- lazily initialise [[Module:Error]]
local yesno -- lazily initialise [[Module:Yesno]]

local p = {}

--------------------------------------------------------------------------------
-- Helper functions
--------------------------------------------------------------------------------

local function getArgs(frame)
        -- Fetches the arguments from the parent frame. Whitespace is trimmed and
        -- blanks are removed.
        mArguments = require('Module:Arguments')
        return mArguments.getArgs(frame, {parentOnly = true})
end

local function removeInitialColon(s)
        -- Removes the initial colon from a string, if present.
        return s:match('^:?(.*)')
end

local function maybeItalicize(s, shouldItalicize)
        -- Italicize s if s is a string and the shouldItalicize parameter is true
        if s and shouldItalicize then
                return '<i>' .. s .. '</i>'
        else
                return s
        end
end

local function parseLink(link)
        -- Parse a link and return a table with the link's components.
        -- These components are:
        -- - link: the link, stripped of any initial colon (always present)
        -- - page: the page name (always present)
        -- - section: the page name (may be nil)
```

```
        -- - display: the display text, if manually entered after a pipe (may be
        link = removeInitialColon(link)

        -- Find whether a faux display value has been added with the {{!}} magic
        -- word.
        local prePipe, display = link:match('^(.-)|(.*)$')
        link = prePipe or link

        -- Find the page, if it exists.
        -- For links like [[#Bar]], the page will be nil.
        local preHash, postHash = link:match('^(.-)#(.*)$')
        local page
        if not preHash then
                -- We have a link like [[Foo]].
                page = link
        elseif preHash ~= '' then
                -- We have a link like [[Foo#Bar]].
                page = preHash
        end

        -- Find the section, if it exists.
        local section
        if postHash and postHash ~= '' then
                section = postHash
        end

        return {
                link = link,
                page = page,
                section = section,
                display = display,
        }
end

local function formatDisplay(parsed, options)
        -- Formats a display string based on a parsed link table (matching the
        -- output of parseLink) and an options table (matching the input options
        -- _formatLink).
        local page = maybeItalicize(parsed.page, options.italicizePage)
        local section = maybeItalicize(parsed.section, options.italicizeSection)
        if (not section) then
                return page
        elseif (not page) then
                return mw.ustring.format('§ %s', section)
        else
                return mw.ustring.format('%s § %s', page, section)
        end
end

local function missingArgError(target)
        mError = require('Module:Error')
        return mError.error{message =
                'Error: no link or target specified! ([[' .. target .. '#Errors|H
        }
end

--------------------------------------------------------------------------------
-- Main functions
--------------------------------------------------------------------------------

function p.formatLink(frame)
        -- The formatLink export function, for use in templates.
        yesno = require('Module:Yesno')
        local args = getArgs(frame)
```

```
	local link = args[1] or args.link
	local target = args[3] or args.target
	if not (link or target) then
		return missingArgError('Template:Format link')
	end

	return p._formatLink{
		link = link,
		display = args[2] or args.display,
		target = target,
		italicizePage = yesno(args.italicizepage),
		italicizeSection = yesno(args.italicizesection),
		categorizeMissing = args.categorizemissing
	}
end

function p._formatLink(options)
	-- The formatLink export function, for use in modules.
	checkType('_formatLink', 1, options, 'table')
	local function check(key, expectedType) --for brevity
		checkTypeForNamedArg(
			'_formatLink', key, options[key], expectedType or 'string
		)
	end
	check('link')
	check('display')
	check('target')
	check('italicizePage', 'boolean')
	check('italicizeSection', 'boolean')
	check('categorizeMissing')

	-- Normalize link and target and check that at least one is present
	if options.link == '' then options.link = nil end
	if options.target == '' then options.target = nil end
	if not (options.link or options.target) then
		return missingArgError('Module:Format link')
	end

	local parsed = parseLink(options.link)
	local display = options.display or parsed.display
	local catMissing = options.categorizeMissing
	local category = ''

	-- Find the display text
	if not display then display = formatDisplay(parsed, options) end

	-- Handle the target option if present
	if options.target then
		local parsedTarget = parseLink(options.target)
		parsed.link = parsedTarget.link
		parsed.page = parsedTarget.page
	end

	-- Test if page exists if a diagnostic category is specified
	if catMissing and (mw.ustring.len(catMissing) > 0) then
		local title = nil
		if parsed.page then title = mw.title.new(parsed.page) end
		if title and (not title.isExternal) and (not title.exists) then
			category = mw.ustring.format('[[Category:%s]]', catMissi
		end
	end

	-- Format the result as a link
	if parsed.link == display then
```

```
                return mw.ustring.format('[[:%s]]%s', parsed.link, category)
        else
                return mw.ustring.format('[[:%s|%s]]%s', parsed.link, display, ca
        end
end

--------------------------------------------------------------------------------
-- Derived convenience functions
--------------------------------------------------------------------------------

function p.formatPages(options, pages)
        -- Formats an array of pages using formatLink and the given options table
        -- and returns it as an array. Nil values are not allowed.
        local ret = {}
        for i, page in ipairs(pages) do
                ret[i] = p._formatLink{
                        link = page,
                        categorizeMissing = options.categorizeMissing,
                        italicizePage = options.italicizePage,
                        italicizeSection = options.italicizeSection
                }
        end
        return ret
end

return p
```

Modul:Format link/Doku

Dies ist die Dokumentationsseite für Modul:Format link

This module, migrated from origins in Module:Hatnote, provides functionality for formatting links for display, including that powering the Vorlage:Tl template.

It can pretty-format section links with the section symbol ("§") and appropriate whitespace, it automatically escapes category and file names with the colon trick, and includes functionality for italicizing the page or section name, and for detecting and categorizing results that produce red links.

Inhaltsverzeichnis

1 Use from wikitext 8
2 Use from other Lua modules 8
2.1 _formatLink 8
2.2 formatPages 9
3 Errors 10

Use from wikitext

The functions in this module cannot be used directly from #invoke, and must be used through templates instead. Please see Template:Format link for documentation on usage of that template.

Use from other Lua modules

To load this module from another Lua module, use the following code:

```
local mFormatLink = require('Module:Format link')
```

You can then use the functions as documented below.

_formatLink

```
mFormatLink._formatLink{
    link = 'Link',
    display = 'Display',
    target = 'Target',
    italicizePage = true,
    italicizeSection = true,
    categorizeMissing = 'Pages using formatted red links'
}
```

Formats *link* as a wikilink. Categories and files are automatically escaped with the colon trick, and links to sections are automatically formatted as *page § section*, rather than the MediaWiki default of *page#section*.

Several options modify the output:

- If the *display* value is present, then it will be used as a display value. Any manual piping (using the {{!}} magic word or similar) present in *link* will be overridden by the *display* value if present.
- If the *target* value is present, then it will override *link* as a target, but the result will still be *displayed* using either the value from *display*, or the result of formatting *link*.
- If *italicizePage* is true, then the page portion of the link is italicized if present.
- If *italicizeSection* is true, then the section portion of the link is italicized if present.
- If *categorizeMissing* is a non-empty string, then that value is used as a category name, and that category will be applied if the resulting target of the link (no matter whether through *link* or through *target*) doesn't exist.

Examples

`mFormatLink._formatLink{link = 'Foo#Bar'}` → [[:Foo#Bar|Foo § Bar]] → Vorlage:Format link

`mFormatLink._formatLink{link = 'Baz', display = 'Qux'}` → [[:Baz|Qux]] → Vorlage:Format link

`mFormatLink._formatLink{link = 'Foo|Bar', display = 'Baz'}` → [[:Foo|Baz]] → Vorlage:Format link

`mFormatLink._formatLink{link = '#Foo', target = 'Example#Foo'}` → [[:Example#Foo|§ Foo]] → Vorlage:Format link

`mFormatLink._formatLink{link = 'The Lord of the Rings#Plot', italicizePage = true}` → [[:The Lord of the Rings#Plot|''The Lord of the Rings'' § Plot]] → Vorlage:Format link

`mFormatLink._formatLink{link = 'Cybercrime Prevention Act of 2012#Disini v. Secretary of Justice', italicizeSection = true}` → [[:Cybercrime Prevention Act of 2012#Disini v. Secretary of Justice|Cybercrime Prevention Act of 2012 § ''Disini v. Secretary of Justice'']] → Vorlage:Format link

`mFormatLink._formatLink{link = 'Nonexistent page', categorizeMissing = 'Example'}` → [[:Nonexistent page]][[Category:Example]] → Vorlage:Format link

`mFormatLink._formatLink{link = 'Existing', categorizeMissing = 'Example'}` → [[:Existing]] → Vorlage:Format link

formatPages

```
mFormatLink.formatPages(options, pages)
```

This derived function is useful for lists that format many links. It formats an array of pages using the _formatLink function, and returns the result as an array. Options in the *options* table are applied, and use the same names as the options for *_formatLink*.

Example

Vorlage:Code → Vorlage:Code

Errors

If *_formatLink* is used and neither a *link* nor a *target* argument is provided, then the module will produce an error message instead of its usual output, as it *cannot* then produce valid output.

You can solve this error by providing appropriate parameters to *_formatLink*, or you may want to ensure that a more descriptive error is provided by a downstream template or module when it would otherwise call *_formatLink* with inadequate arguments.