

# Modul:Hatnote list/Doku

---

Dies ist die Dokumentationsseite für **Modul:Hatnote list**

Vorlage:Used in system

Inhaltsverzeichnis	
1 Usage from wikitext .....	1
2 Usage from Lua .....	1
2.1 andList .....	1
2.2 orList .....	1
2.3 forSee .....	1

## Usage from wikitext

---

This module is not designed be used directly from wikitext even though `forSee` does take an initial frame argument and could potentially be used from wikitext, e.g.:

- `{{hatnote|PREFIX {{#invoke:Hatnote list|forSee|{{tl|For}}|Module:For|{{tl|About}}|Module:About}} POSTFIX}}` → [Vorlage:Hatnote](#)

## Usage from Lua

---

To call the module, use

```
local mHatList = require('Module:Hatnote list')
```

or similar, then access its methods through the `mHatList` variable (or whatever was used).

## andList

---

`andList` takes a list in table form, and returns a string with the list separated with "and" and commas as appropriate.

## orList

---

`orList` takes a list in table form, and returns a string with the list separated with "or" and commas as appropriate.

## forSee

---

`_forSee` takes three arguments: a table of trimmed arguments with blanks removed, a "from" number with the index to start at, and an options table, and returns a string with a number of "For X, see [[Y]]" sentences. The links are formatted using the methods from [Module:Hatnote](#).



As a convenience, the `forSee` method (without the leading underscore) takes the same arguments except with a frame instead of an args table, using `getArgs()` from [Module:Arguments](#) to preprocess the arguments.