Inhaltsverzeichnis

Modul:Hatnote list/Doku

Dies ist die Dokumentationsseite für Modul:Hatnote list

Vorlage:Used in system

Inhaltsverzeichnis

- 1 Usage from wikitext
- 2 Usage from Lua
  - 2.1 andList
  - 2.2 orList
  - 2.3 forSee

Usage from wikitext

This module is not designed be used directly from wikitext even though `forSee` does take an initial `frame` argument and could potentially be used from wikitext, e.g.:

- `{{hatnote|PREFIX {{#invoke:Hatnote list|forSee|{{tl|For}}|Module:For|{{tl|About}}|Module:About}} POSTFIX}}` Vorlage:Hatnote

Usage from Lua

To call the module, use

```
local mHatList = require('Module:Hatnote list')
```

or similar, then access its methods through the `mHatList` variable (or whatever was used).

andList

`andList` takes a list in table form, and returns a string with the list separated with "and" and commas as appropriate.

orList

`orList` takes a list in table form, and returns a string with the list separated with "or" and commas as appropriate.

forSee

`_forSee` takes three arguments: a table of trimmed arguments with blanks removed, a "from" number with the index to start at, and an options table, and returns a string with a number of `"For X, see [[Y]]"` sentences. The links are formatted using the methods from Module:Hatnote.

As a convenience, the `forSee` method (without the leading underscore) takes the same arguments except with a frame instead of an args table, using `getArgs()` from Module:Arguments to preprocess the arguments.