Inhaltsverzeichnis

1. Modul:Lua banner 2
2. Modul:Lua banner/Doku 5

Modul:Lua banner

Vorlage:Lua This module implements the Vorlage:Tl template.

Usage from wikitext

This module cannot be used directly from wikitext. It can only be used through the Vorlage:Tl template. Please see the template page for documentation.

Usage from Lua modules

To use this module from other Lua modules, first load the module.

```
local mLuaBanner = require('Module:Lua banner')
```

You can then generate a side box using the _main function.

```
mLuaBanner._main(args)
```

The *args* variable should be a table containing the arguments to pass to the module. To see the different arguments that can be specified and how they affect the module output, please refer to the Vorlage:Tl template documentation.

Tracking category

- Vorlage:Clc

```
-- This module implements the {{lua}} template.
local yesno = require('Module:Yesno')
local mList = require('Module:List')
local mTableTools = require('Module:TableTools')
local mMessageBox = require('Module:Message box')

local p = {}

function p.main(frame)
	local origArgs = frame:getParent().args
	local args = {}
	for k, v in pairs(origArgs) do
		v = v:match('^%s*(.-)%s*$')
		if v ~= '' then
			args[k] = v
		end
	end
	return p._main(args)
end

function p._main(args)
	local modules = mTableTools.compressSparseArray(args)
```

```
	local box = p.renderBox(modules)
	local trackingCategories = p.renderTrackingCategories(args, modules)
	return box .. trackingCategories
end

function p.renderBox(modules)
	local boxArgs = {}
	if #modules < 1 then
		boxArgs.text = '<strong class="error">Error: no modules specifie
	else
		local moduleLinks = {}
		for i, module in ipairs(modules) do
			moduleLinks[i] = string.format('[[:%s]]', module)
		end
		local moduleList = mList.makeList('bulleted', moduleLinks)
		local title = mw.title.getCurrentTitle()
		if title.subpageText == "doc" then
			title = title.basePageTitle
		end
		if title.contentModel == "Scribunto" then
			boxArgs.text = 'This module depends on the following othe
		else
			boxArgs.text = 'This template  uses [[Wikipedia:Lua|Lua]]
		end
	end
	boxArgs.type = 'notice'
	boxArgs.small = true
	boxArgs.image = '[[File:Lua-logo-nolabel.svg|30px|alt=|link=]]'
	return mMessageBox.main('mbox', boxArgs)
end

function p.renderTrackingCategories(args, modules, titleObj)
	if yesno(args.nocat) then
		return ''
	end

	local cats = {}

	-- Error category
	if #modules < 1 then
		cats[#cats + 1] = 'Lua templates with errors'
	end

	-- Lua templates category
	titleObj = titleObj or mw.title.getCurrentTitle()
	local subpageBlacklist = {
		doc = true,
		sandbox = true,
		sandbox2 = true,
		testcases = true
	}
	if titleObj.namespace == 10
		and not subpageBlacklist[titleObj.subpageText]
	then
		local category = args.category
		if not category then
			local categories = {
				['Module:String'] = 'Lua String-based templates',
				['Module:Math'] = 'Templates based on the Math Lu
				['Module:BaseConvert'] = 'Templates based on the
				['Module:Citation'] = 'Lua-based citation templat
			}
			categories['Module:Citation/CS1'] = categories['Module:Ci
			category = modules[1] and categories[modules[1]]
```

```
                        category = category or 'Lua-based templates'
                end
                cats[#cats + 1] = category
                local protLevels = {
                        autoconfirmed = 1,
                        extendedconfirmed = 2,
                        templateeditor = 3,
                        sysop = 4
                }
                local currentProt
                if titleObj.id ~= 0 then
                        -- id is 0 (page does not exist) if am previewing before
                        currentProt = titleObj.protectionLevels["edit"][1]
                end
                if currentProt == nil then currentProt = 0 else currentProt = pro
                for i, module in ipairs(modules) do
                        local moduleProt = mw.title.new(module).protectionLevels[
                        if moduleProt == nil then moduleProt = 0 else moduleProt
                        if moduleProt < currentProt then
                                cats[#cats + 1] = "Templates using under-protecte
                                break
                        end
                end
        end

        for i, cat in ipairs(cats) do
                cats[i] = string.format('[[Category:%s]]', cat)
        end
        return table.concat(cats)
end

return p
```

Modul:Lua banner/Doku

Dies ist die Dokumentationsseite für Modul:Lua banner

Vorlage:Lua This module implements the Vorlage:Tl template.

Usage from wikitext

This module cannot be used directly from wikitext. It can only be used through the Vorlage:Tl template. Please see the template page for documentation.

Usage from Lua modules

To use this module from other Lua modules, first load the module.

```
local mLuaBanner = require('Module:Lua banner')
```

You can then generate a side box using the _main function.

```
mLuaBanner._main(args)
```

The *args* variable should be a table containing the arguments to pass to the module. To see the different arguments that can be specified and how they affect the module output, please refer to the Vorlage:Tl template documentation.

Tracking category

- Vorlage:Clc