Modul:Namespace detect/Doku

Dies ist die Dokumentationsseite für Modul:Namespace detect

This module allows you to output different text depending on the namespace that a given page is in. It is a Lua implementation of the Vorlage:Tl template, with a few improvements: all namespaces and all namespace aliases are supported, and namespace names are detected automatically for the local wiki.

Inhaltsverzeichnis

1 Usage 1
2 Parameters 1
2.1 Namespace parameters 2
3 Table function 3
4 Porting to different wikis 3
5 Technical details 3

Usage

```
{{#invoke: Namespace detect | main
| page              = <!-- page to detect namespace for, if not the current page
| main              = <!-- text to return for the main namespace -->
| talk              = <!-- text to return for talk namespaces -->

<!-- text to return for specific subject namespaces -->
| portal            =
| category          =
| user                    =
| wikipedia         =
| mediawiki         =
| book              =
| timedtext         =
| template          =
| special           =
| media             =
| file              =
| image             =
| help                    =
| module            =

| other             = <!-- text to return for unspecified namespaces -->
| demospace         = <!-- namespace to display text for -->

| subjectns         = <!-- set to "yes" to treat talk pages as the corresponding
}}
```

Parameters

- **main** - text to return if the page is in the main namespace.

- **talk** - text to return if the page is in a talk namespace. This can be any talk namespace - it will match any of "Talk:", "Wikipedia talk:", "User talk:", etc.
- Subject namespace parameters, e.g. **wikipedia**, **user**, **file**... - the text to return if the page is in the corresponding namespace. This module accepts all subject namespaces as parameters, including namespace aliases and virtual namespaces. See below for a list of supported values.
- **other** - text to return if no parameters for the page's namespace were specified. This text is also returned if Vorlage:Para is set to an invalid namespace value.
- **subjectns** - if on a talk page, use the corresponding subject page. Can be set with values of "yes", "y", "true" or "1".
- **demopage** - specifies a page to detect the namespace of. If not specified, and if the Vorlage:Para parameter is not set, then the module uses the current page.
- **demospace** - force the module to behave as if the page was in the specified namespace. Often used for demonstrations.

Namespace parameters

Possible values for subject namespace parameters are as follows:

Namespace	Aliases
main	
benutzer	user, benutzerin
projekt	project
datei	file, bild, image
mediawiki	
vorlage	template
hilfe	help
kategorie	category
attribut	property
formular	form
konzept	concept
smw/schema	smw/schema
rule	
widget	
campaign	
timedtext	
modul	module
blog	
socialentity	
gadget	

Namespace	Aliases
gadget-definition	gadget definition
copikiblog	
deutsch	
english	
français	
italiano	
español	
nederlands	
slovenská	
dansk	
polska	
suomi	

Table function

Use the following to display a table with the different possible namespace parameters:

```
{{#invoke:Namespace detect|table|talk=yes}}
```

To include the parameter for talk namespaces, use Vorlage:Para.

Porting to different wikis

This module is designed to be portable. To use it on a different wiki, all you need to do is to change the values in Module:Namespace detect/config. Instructions are available on that page.

Technical details

The module uses a data page at Module:Namespace detect/data. This page is loaded with mw.loadData, which means it is processed once per page rather than once per #invoke. This was done for performance reasons.