# Inhaltsverzeichnis

1. Modul:RoundN ..... 2
2. Modul:RoundN/Doku ..... 22

# Modul:RoundN

**Inhaltsverzeichnis**

1 Usage ..... 2
2 Parameter List ..... 2
2.1 Example 1 ..... 3
2.2 Example 2 ..... 5
3 Node Functions ..... 7
4 Undocumented features ..... 8
4.1 Partial List of undocumented params ..... 8

## Usage

This is a module for meta templates such as Vorlage:Tl, Vorlage:Tl, etc. Though originally designed for sports, it can be used to present any tree.

Basic form:

```
{{#invoke:RoundN|main|columns = [number of columns (3 columns for Round8, 4 colun
```

Alternatively, the shorthand form `{{#invoke:RoundN|N16}}` (or any power of 2 between N2 and N512) is equivalent to Vorlage:Code

## Parameter List

- Vorlage:Red parameter names are required.
- *italicized* parameter names are required in some cases
- Vorlage:Blue parameter names involve new features not available prior to the release of this module

| Parameter name | Description |
|---|---|
| Vorlage:TOC tab | Number of columns/eliminations (3 columns for Round8, 4 columns for Round16, etc.)<br><br>**Note**<br><br>• For `columns` *less than 4* (i.e. Round2-Round8), the 3rd Place match box is hidden by default. For `columns` *greater or equal to 4*, the 3rd Place match box is visible by default. This reflects the behavior of the templates prior to this module's release. |

| Parameter name | Description |
|---|---|
| | Vorlage:TOC tab While required for invoking the main function (`{{#invoke:RoundN|main|columns=}}`), this module has meta functions in the form of 'N##' which can call main with the right Vorlage:Code for you. For example, you may replace `...|main|columns = 7...` with `...|N128 ...`. Valid for N# where # is a power of 2. You must invoke this module directly to use this (vs. a template that already has a columns value). Only works up to N512. If say N1024 ever becomes necessary, call main directly and set Vorlage:Para.<br><br>PS: Though adding shorthands up to N ~70 trillion would be easy, it would make unnecessary overhead as these meta functions are generated eached time this module is called (granted generating such functions up to ~70 trillion is probably less expensive than making the table for columns = 3). |
| Vorlage:TOC tab | Unnamed parameters (i.e. a value not prefixed by `[param_name] =`) are read sequentially in groups of 5 such that:<br><br>**Example 1**<br><br>Vorlage:Demo Placing each group of 5 on a new line is optional, but does make it easier to read. Also, consider adding the comments such as `<!-- Date-Place/Team 1/Score 1/Team 2/Score 2 -->` on top and `<!-- Finals -->` above the first group of 5 in the finals round, etc. |
| Vorlage:TOC tab | Set the `style` parameter to add custom CSS to the table.<br><br>Modul Diskussion:RoundN/testcases/1 |
| Vorlage:TOC tab | For large tables, set Vorlage:Code to the desired height in pixels.<br><br>Modul Diskussion:RoundN/testcases/1<br><br>CSS units are also allowed (i.e. '20em', '30%', etc.). |

| Parameter name | Description |
|---|---|
| | **Note** This works by duplicating the entire table and then using CSS to lock the clone of the table to the top of the div. Conceivably, for extremely large tables, this can result in a significant amount of extra HTML code to download versus if Vorlage:Code is used. |
| Vorlage:TOC tab | If it is desirable to have the round heading scroll with the table (such as if a larger viewing area is desired), set Vorlage:Code to 'yes'<br><br>Modul Diskussion:RoundN/testcases/1 |
| Vorlage:TOC tab | If set, boxes for the #th match group will not be shown. Most often used for playoffs or when the number of teams playing in the first round is not a power of 2.<br><br>Modul Diskussion:RoundN/testcases/1 Vorlage:TOC tab: The shorthand `\|skipmatch = 1-2;4;6-7` will do the same thing as:<br><br>`\|skipmatch1=yes`<br>`\|skipmatch2=yes`<br>`\|skipmatch4=yes`<br>`\|skipmatch6=yes`<br>`\|skipmatch7=yes`<br><br>**Note:**<br><br>• Unlike in the original templates, this module does not require leading zeroes in this parameter, i.e. skipmatch001 is the same as skipmatch1 (though it may make your template code easier to read if lead with an appropriate number of zeroes).<br>• The 5 parameters that would have populated the skipped box will be ignored regardless of value unless `omit_blanks` is set to 'yes' (see below).<br>• Previously, skipmatch only worked in the first round. This limitation no longer applies. (See Module talk:RoundN/testcases/3) |
| Vorlage:TOC tab | |

| Parameter name | Description |
|---|---|
| | If `omit_blanks` is set to yes, then all parameters that would have been skipped will instead be shifted to the next non-skipped box. (This is turned off by default because most templates made before the release of this module were required to use empty parameters as placeholders.)<br><br>Modul Diskussion:RoundN/testcases/1 |
| Vorlage:TOC tab | The Vorlage:Code parameter accepts either Vorlage:Code or Vorlage:Code, which will automatically bold the text of the participant with the *higher* or *lower* score, respectively. In other words, set this to 'low' if the lower score wins and 'high' if the high score wins.<br><br>**Example 2**<br><br>Modul Diskussion:RoundN/testcases/2 **Note:**<br><br>• If entering a score that includes non-numbersVorlage:--such as `3 (6)`, the Semi Final score for team C in the above exampleVorlage:--the module will first remove all non-digit characters and concatenate the rest. For example, `3 (5)` and `3 (6)` would be converted to `35` and `36`, respectively, before being compared. This should be valid for most cases, however, you may override using the `manualboldmatch##` parameter.<br>• If the scores are tied or contain no numbers, then neither will be bolded, however, you may still manually bold them with wikimarkup.<br>• This does not remove any formatting already present. |
| Vorlage:TOC tab | Modul Diskussion:RoundN/testcases/2<br><br>Vorlage:TOC tab The form `manualboldmatch = 1-3;6;9-12` is also available. |
| Vorlage:TOC tab | Set `\|previewnumbers = yes` to show numbers next to each match group (useful for Vorlage:Code and Vorlage:Code) when viewing on the template page. |

| Parameter name | Description |
|---|---|
| | Note that these numbers will not appear in article space. |
| Vorlage:TOC tab | Use `RD#`, replacing # with the desired column such that 1 is the leftmost round and X is the rightmost when `columns = X`. For example:<br><br>Vorlage:Demo **Note** RD[N+1] = Third Place, and will perform the job of the `Consol` parameter if the latter is omitted, i.e. RD[N+1] is ignored if Consol is true. Also, this alternate name for Consol was not available prior to the release of this module (and is provided because the module's programmer thought 'Consol' was unintuitive). |
| Vorlage:TOC tab | By default, `\|3rdplace=` is set to 'yes' when `columns` is greater than 3 and 'no' otherwise. Override as desired. (See `Consol` if you wish to rename this heading)<br><br>Vorlage:Demo |
| Vorlage:TOC tab | Set `Consol=name` to change the 'Third Place' label to 'name'. You may also use the form RD# where # = columns + 1.<br><br>Vorlage:Demo |
| Vorlage:TOC tab | Add `\|color=yes`<br><br>Final<br>7<br>Gold medalist 3<br>Silver medalist 2<br><br>Third place<br>8<br>Bronze medalist 1<br>0 |
| Vorlage:TOC tab | Set `team-width` to the desired width in pixels. (Default is 170) |
| Vorlage:TOC tab | Set `score-width` to the desired width in pixels. |

| Parameter name | Description |
|---|---|
| | (Default is 30) |
| Vorlage:TOC tab | Setting `\|widescore=yes` is basically equal to `\|score-width=40`. Provided for compatibility. Ignored if `score-width` is set. |
| Vorlage:TOC tab | Set `score-boxes` to the desired number of score boxes per match. (Default is 1). The number can be followed by `+ sum`, which will add one more score box with the sum of all the others. For examples, see test case 5 and test case 6. |
| Vorlage:TOC tab | Set `\|template=yes` if used to create a template for a specific game (add V.T.E. link using Vorlage:Tl). |
| Vorlage:TOC tab | Set `\|flex_tree=yes` to make the brackets more compact. That is, to have less space between matches of the same round. |

## Node Functions

Vorlage:Ombox

For greater customization, node functions may be added to the parameter usually used for providing match information such as dates and location. Simply insert `node_function{`*`function name`*`}` in the appropriate location. A demonstration of most of the node functions can be found at RoundN/testcases/4.

- **orphan** - Current node is disconnected from all other nodes (no lines will be drawn). One practical use for this may be when the winners of the previous round advance to a different tournament instead of playing each other but the losers still play a consolation match for 3rd place, as per this discussion.

For the next three node functions, the parameters usually used for team names and scores should be omitted if these node functions are used.

- **line** - Current node is omitted and replaced with a horizontal line. Text may be displayed above this line via `node_function{line(`*`text`*`)}` (at some point, the preferred format would be `node_function{line}`*`text`* to match the form of the canvas function though backwards compatibility would probably be maintained). If curly brackets are desired in the text, make sure to escape them with `\`.
- **bridge** - Current node is omitted and replaced with a vertical line.
- **canvas** - Current node is replaced with whatever you want via `node_function{canvas}` *`anything`*

- **heading** - Not yet implemented. Planned node function with the form `node_function {heading(*name*)}*date/location*`. Makes a round name heading like for the Consol parameter, but may be placed anywhere, as per the "Elimination Rounds" of RoundN/testcases/6 (which currently renders the planned output of this function without the functions).

## Undocumented features

Alas User:Codehydro seriously overbuilt this module and never found the time to document even half the features available. Check out the following examples which may contain some advanced features: Spezial:PrefixIndex/Module talk:RoundN/testcases

## Partial List of undocumented params

- no_column_head
- short_brackets
- branch_upwards

Note that some of these features may not have been documented due to incomplete implementation.

---

```
local p = {
        RD = {
                'Quarter-finals',
                'Semi-finals',
                'Final',
                'Third place'
        },
        bgColor = {head = '#f2f2f2', 'gold', 'silver', '#C96', '#f9f9f9'},
        reuseStr = {},
        saveStr = function(self, name, ...)
                if not self.reuseStr[name] then
                        self.reuseStr[name] = table.concat{...}
                end
                return self.reuseStr[name]
        end
}

--Provides a convenient naming shortcut up to {{#invoke:RoundN|N512}} = {{invoke:
for columns = 1, 9 do
        local N = math.pow(2, columns)
        p['N' .. N] = function(frame)
                return p.main(frame.args, columns)
        end
        p['n' .. N] = p['N' .. N]--to make case insensitive
end

--saves memory and avoids errors when using a nil as a table by providing a tempo
p.nilAsTab = {
        __index = function(t, i)
                return setmetatable({}, setmetatable(p.nilAsTab, {__index = {t =
        end,
        __newindex = function (pt, pi, v) --store new values in actual table rath
                rawset(p.nilAsTab.t, p.nilAsTab.i, {})[p.nilAsTab.i][pi] = v
                setmetatable(p.nilAsTab.t[p.nilAsTab.i], {__call = p.nilAsTab.__c
```

```
	end,
	__call = function(t, i)
		return t and rawget(t, i)
	end
}
--never assign a value to these or they will stop being empty
local infiniteEmpty = setmetatable({}, {__index = setmetatable({}, p.nilAsTab), p
local callableEmpty = setmetatable({}, p.nilAsTab)

local rowNum, head, m, col, tab, esc = {}, {}, {num = 1, phase = 0, bold = infini
	bs = require'Module:Escape',--backslash
	comma = {['(%([^,]*),([^%)]*%))'] = '%1|@!#|%2'},--escape commas in ()
}
local nodeFunc = {
	scanPattern = function(self, args, step)
		self.pattern = nil
		if args[step] then
			self.pattern, self.nonFunc = string.match(esc.bs:text(arg
		end
		if self.pattern then
			for k, v in pairs(esc.comma) do
				self.pattern = self.pattern:gsub(k, v)
			end
			self.nonFunc = self.nonFunc and esc.bs:undo(self.nonFunc)
			self.pattern = mw.text.split(self.pattern, '%s*,%s*')
			for k, v in ipairs(self.pattern) do
				local func, arg = string.match(v, '^(%w+)%(?([^%)
				if func and self[func] and self[func].main then
					self.pattern[k] = func
					if arg then
						for x, y in pairs(esc.comma) do
							arg = esc.bs:undo(arg):gs
						end
						self[func].arg = self[func].arg
						self[func].arg[m.num] = arg
					end
				end
			end
		end
		return self.pattern
	end,
	helper = {
		topBranch = function()--node is top of fork if top is 0
			return (m.num - col.top) % 2
		end,
		addText = function(text)
			if text and text ~= '' then
				tab.r:wikitext(text)
			end
		end
	},
	line = {--this node is omitted and replaced with a line
		main = function(x)
			local h = p.getNodeFunc()
			if m.available then
				local text, topId, isTop, notTop = h.line.arg[m.r
				isTop = topId == 0
				notTop = {[isTop and 1 or 0] = p.reuseStr.solid}
				for k = 0, 1 do
					tab.r = rowNum[m.r + k * 4]:tag'td'
					:css(notTop[k] and
						{[isTop and 'border-top'
						or {}
					)
```

```
                                                :attr{
                                                        rowspan = ({[0] = 4, 2})
                                                        colspan = p.colspan
                                                }
                                        h.addText(text or h.nonFunc)
                                        text = nil
                                end
                                m.available = false
                        else
                                return nil
                        end
                        return x
                end
        },
        bridge = {--Draw a line to the neighboring node in the same column that i
                main = function(x)
                        local h = p.getNodeFunc()
                        h.bridge.lay[col.c][m.num - col.top + 1 + (h.topBranch()
                        h.addText(nonFunc)
                        return x
                end,
                lay = setmetatable({}, p.nilAsTab)
        },
        canvas = {--Merges all cells in node. Content will be the next parameter
                main = function(x)
                        local h = p.getNodeFunc()
                        if m.available then
                                tab.r = rowNum[m.r]:tag'td'
                                        :attr{
                                                rowspan = 6,
                                                colspan = p.colspan
                                        }
                                h.addText(h.nonFunc)
                                m.available = false
                                return x
                        else
                                return nil
                        end
                end
        },
        orphan = {--sets a flag for skipMatch to be set by p._main
                main = function(x)
                        p.getNodeFunc().orphan.num = m.num
                        return x
                end
        },
        skipAllowed = {--table of supported node functions when node is skipped (
                bridge = true,
                canvas = true
        }
}

setmetatable(nodeFunc.helper, {__index = nodeFunc})
function p.getNodeFunc()
        return nodeFunc.helper
end

local function newRow(bodyRow)
        local first = p.flex_tree.merge and mw.clone(p.flex_tree.cell) or p.flex_
        tab.r = tab:tag'tr'
                :node(first)
        if bodyRow then
                table.insert(rowNum, bodyRow, tab.r)
                if p.flex_tree.merge then
```

```
                        rowNum[bodyRow].first = first
                        rowNum[bodyRow].first.unchanged = true
                end
        end
end

local function drawHead(text, row3rd)
        local td = (row3rd and rowNum[row3rd]:tag'td':attr{rowspan = 2}
                or head.row:tag'td')
                :attr{colspan = p.colspan}
        if text ~= 'omit_label' then
                td:wikitext(text):css{
                        ['text-align'] = 'center',
                        border = '1px solid #aaa',
                        background = p.bgColor.head
                }
        end
end

local function spacer(width)
        tab.r:tag'td'
                :attr{width = width}
                :wikitext(p.no_column_head and '' or ' ')
end

local function dpBox(v, r)
        p.dpBoxBase = p.dpBoxBase or mw.html.create'td':attr{rowspan = 2, colspar
        if not v then
                p.dpBoxEmpty = p.previewnumbers and mw.clone(p.dpBoxBase) or p.dp
                rowNum[r]:node(p.dpBoxEmpty)
        else
                rowNum[r]:node(mw.clone(p.dpBoxBase):wikitext(v))
        end
end

p.scoreWasher = {
        numberFormat = '%-?%d+%.?%d*',
        main = function (self, s)
                if s then
                        for _, cycle in ipairs(self.cycles) do
                                s = s:gsub(unpack(cycle))
                        end
                        if p.scoreSumBox and self.plus then
                                local t = 0
                                for _, part in ipairs(mw.text.split(s, self.plus)
                                        t = t + (tonumber(part:match('%-?%d+%.?%d
                                end
                                return t
                        end
                        return tonumber(s:match(self.numberFormat)) or math.huge
                end
                return 0
        end,
        spin = function(self, v)
                table.insert(self, v)
                return self
        end,
        load = function (self, cycle)
                local wash, rinse = 0, {spin = self.spin}
                for v in cycle:gfind('%(([^%(%)]-)%)') do
                        if v == '_plus_' then
                                self.plus = v
                                rinse:spin(v)
                                cycle = cycle:gsub('%(_plus_%)', '', 1)
```

```
                        else
                                wash = wash + 1
                                rinse:spin('%'):spin(wash)
                        end
                end
                table.insert(self.cycles, {esc.bs:undo(cycle, '%%'), table.concat
        end,
        init = function(self, setting)
                self.cycles = {original = setting}
                for cycle in (setting and esc.bs:text(setting) or '{<.->} {[^%d]*
                        self:load(cycle)
                end
        end,
                sum = function (clean)
                local sum = {0, 0}
                for _, box in ipairs(clean) do
                        for team, score in ipairs(box) do
                                sum[team] = sum[team] + score
                        end
                end
                return unpack(math.max(unpack(sum)) == math.huge and {'&mdash;',
        end
}

local function boldWin(s1, s2)
        return setmetatable(
                p.bold and s1 ~= s2 and (math[({'min', 'max'})[p.bold]](s1, s2) =
                p.nilAsTab
        )
end

local function maxSpan(span, start, rows)
        return math.min(span, math.max(0, rows - start + 1))
end

--in case of templates like RDseed need padding value
p.teamBoxPadding = function()
        return '.6ex'
end
p.teamBoxPadTab = {padding = '0 ' .. p.teamBoxPadding()}
p.teamBoxNormal = {border = '1px solid #aaa', background = p.bgColor[4]}
local function teamBox(v, r, f)
        if p.flex_tree.merge and not v and f.phase == 2 then
                for i = -2, 0 do
                        if rowNum[r + i].first.unchanged then
                                rowNum[r + i].first.unchanged = nil
                                rowNum[r + i].first:node(p.unflex_div)
                        end
                end
                tab.r:attr{rowspan = 4}:css{['vertical-align'] = 'center'}
        else
                if not p.bold then
                --backwards compatability (wikitemplates bold each arg individual
                        local hasBold, b = tostring(v):gsub("([^']*)'''([^']*)",
                        if b == 1 then
                                v = hasBold
                        end
                end
                local cell
                if f[1] then
                        cell = f.sumBox and f.sumBox[1] and
                                {padding = f.sumBox[1]}
                                or {['border-left'] = f.borderLeft}
                        cell['text-align'] = v and f[1]
```

```
                else
                        cell = p.teamBoxPadTab
                end
                tab.r = rowNum[r]:tag'td'
                        :css(p.teamBoxCSS)
                        :css(cell)
                        :attr{rowspan = 2}
                        :node(mw.html.create(f.bold and 'b'):wikitext(v or f[1] a
        end
end

function p._main(args)
        function args:clean(key, params)--prevent html comments from breaking nam
                params = params or {}
                local clean = args[key] or params.ifNil
                if clean then
                        params.append = params.append or ''
                        clean = mw.text.decode(clean):gsub('<!%-.-%->', ''):gsub(
                        clean = clean ~= params.append and clean or params.ifNil
                end
                args[key] = params.keepOld and args[key] or clean
                return clean
        end
        p.cols = tonumber(args:clean('columns', {pattern = '%D'}))
        p.tCols = (tonumber(args:clean('final_RDs_excluded', {pattern = '%D'})) o
        local matchPer = {
                pattern = '%d*per%d+[%-x]%d+',
                vals = '(%d*)per(%d+)([%-x])(%d+)'
        }
        local skipMatch, unBold  = {}, {}--(skip|manualbold)match# to boolean
        for k, _ in pairs(args) do
                local mType, mNum = string.match(k, '^(%l+)match(%d*)$')
                mType, mNum = ({skip = skipMatch, manualbold = unBold})[mType], t
                if mType then
                        if mNum then
                                mType[mNum] = args:clean(k) == 'yes' or args[k] =
                        else
                                for pattern in args:clean(k, {ifNil = ''}):gfind(
                                        local d1, period, op, d2 = pattern:match(
                                        d1 = tonumber(d1) or 1
                                        d2 = op == '-' and d2 or (d1 + period * (
                                        for y = d1, d2, period do
                                                mType[y] = true
                                        end
                                end
                                for _, x in ipairs(mw.text.split(args[k]:gsub(mat
                                        x = mw.text.split(x, '-')
                                        for y = tonumber(x[1]) or 1, tonumber(x[2
                                                mType[y] = true
                                        end
                                end
                        end
                end
        end
        for _, v in ipairs({--more args to boolean
                'widescore',
                'template',
                'article_include',
                'color',
                '3rdplace',
                'omit_blanks',
                'scroll_head_unlock',
                'previewnumbers',
                'flex_tree',
```

```
		'no_column_head',
		'short_brackets',
		'branch_upwards'
	}) do
		if args[v] and (p[v] == nil or type(p[v]) == 'boolean') then
			p[v] = args:clean(v) == 'yes' or args[v] == 'true'
		end
	end
	p.namespace = mw.title.getCurrentTitle().namespace
	p.previewnumbers = p.namespace ~= 0 and p.previewnumbers
	p.scoreWasher:init(args['score-clean'])
	p.scoreWasher.demo = args.demoWash and tonumber(args:clean('demoWash', {p
	p.scoreSumBox = args['score-boxes'] and args['score-boxes']:match('%d ?%+
	p.bold = ({low = 1, high = 2})[args:clean('bold_winner')] or p.scoreSumBo
	local sumBox = p.scoreSumBox and 1 or 0
	p.scoreBoxes = (tonumber(args:clean('score-boxes', {pattern = '%D'})) or
	p.scoreSumBox = p.scoreBoxes > 0 and p.scoreSumBox or nil
	local boxStyle = p.scoreBoxes > 1 and
		(p.scoreSumBox and
			setmetatable(
				{{}, [p.scoreBoxes] = {'0 1ex'}},
				{__call = function(t, i) if t[i] then return nil
			)
			or setmetatable(
				{},
				{__call = function() return 0 end}
			)
		)
		or setmetatable({}, {__call = function() return nil end})
	p.colspan = p.scoreBoxes > 0 and (p.scoreBoxes + 1) or nil
	local nodeArgs = {
		score = p.scoreBoxes - sumBox,
		team = {offset = 1 + p.scoreBoxes - sumBox}
	}
	nodeArgs.all = 1 + nodeArgs.team.offset * 2
	nodeArgs.tableSum = {
		__add = function(v, t)
			if #t == 3 then
				return v + nodeArgs.all
			end
			local s = v
			for i, n in ipairs(t) do
				s = s + n
			end
			return s--[[ + (p.scoreSumBox and #t == 3 and -2 or 0) -
		end
	}
	nodeArgs.team[1] = 1--constant to be replaced later by new param
	nodeArgs.team[2] = nodeArgs.team[1] + nodeArgs.team.offset
	nodeArgs.blank = setmetatable({}, nodeArgs.tableSum)
	p.unflex_div = mw.html.create'div'
					:css{overflow = 'hidden', height = '1ex'}
					:wikitext' '
	p.flex_tree = setmetatable({},{__index = {
		merge = p.flex_tree and p.scoreBoxes == 0,
		wt = p.flex_tree and '' or ' ',
		cell = mw.html.create'td'
			:node(not p.flex_tree and p.unflex_div or nil)
	}})
	if args:clean'scroll_height' then
		local fontSize, fontUnit = args.style and args.style:match('font%
		if fontSize then
			local units = {
				em = 1,
```

```
                                ex = 2,
                                ['%'] = 0.01
                        }
                        fontSize, fontUnit = {fontSize * fontUnit}
                end
        end
        tab
                :cssText(table.concat{args.scroll_height and 'padding' or 'margi
                :attr{cellpadding = 0, cellspacing = 0}
        if not p.no_column_head then--headings row
                newRow()
                head.row = tab.r
                        :css{['white-space'] = args.scroll_height and 'nowrap'}
                newRow()
        else
                tab.r = tab:tag'tr'
                tab.r:tag'td'
        end
        local sp = {--set column widths
                args['team-width'] or 170,
                p.widescore and 40 or 30,
                p.short_brackets and 6 or 15,
                p.short_brackets and 4 or 20
        }
        local scoreWidth = args:clean('score-width', {pattern = '[^%d;]'}) and mw
        scoreWidth[1] = tonumber(scoreWidth[1], 10)
        if p.scoreSumBox and #scoreWidth ~= 1 then
                local _scoreWidth = {}
                for k = 1, p.scoreBoxes - 1 do
                        _scoreWidth[k] = tonumber(scoreWidth[k], 10) or math.cei
                end
                setmetatable(scoreWidth, _scoreWidth)
        end
        if p.template or p.article_include then
                p.template = mw.title.new(args.name)
                p.templateFixedName = (p.template.namespace == 0 and not p.articl
        end
        p.template = p.template and mw.title.new(args:clean('name', {pattern = '
        local head_br = {
                count = 0,
                compare = function (self, text)
                        if text and args.scroll_height then
                                local _, count = text:gsub('<br[ >/]', '%1')
                                self.count = math.max(self.count, count)
                        end
                        return text
                end
        }
        p.branch_upwards = p.branch_upwards and 0
        for k = 1, p.cols do
                if k > 1 then
                        spacer(sp[3])
                        spacer(sp[4])
                        if not p.no_column_head then
                                head.row:tag'td':attr{colspan = 2}
                        end
                end
                spacer(sp[1])
                for s = 1, p.scoreBoxes do
                        spacer(#scoreWidth == 1 and scoreWidth[1] or scoreWidth[s
                end
                if not p.no_column_head then
                        head.wt = head_br:compare(args:clean('RD' .. k, {pattern
                                or p.RD[#p.RD + k - p.tCols - 1]
```

```
                        or ('Round of ' .. math.pow(2, p.tCols - k + 1))
                drawHead(
                        k == 1 and p.template and mw.getCurrentFrame():ex
                                title = 'navbar-header',
                                args = {head.wt, p.templateFixedName}
                        } or head.wt
                )
        end
end
sp.row = tab.r
col.tot = math.pow(2, p.tCols - 1)
local step, bump, bumpBase, rows = 1, 0, mw.html.create'td':attr{colspan
args.line_px = table.concat{args:clean('line_px') or 3, args.line_px ~= '
tab.line = {--reduces concats and 'or' statements
        {
                [true] = args.line_px,
                [false] = 0
        },
        args.line_px:rep(2):gsub('(%a)(%d)', '%1 %2', 1)
}
p['3rdplace'] =  p.tCols == p.cols and (p['3rdplace'] or p.cols > 3 and r
if p['3rdplace'] then
        p.textThird = args.Consol or args['RD' .. (p.cols + 1)] or p.RD[4
        local no3rdText = p.no_column_head or p.textThird and p.textThird
        rowNum.third = math.max(math.pow(2, p.branch_upwards and -3 or p.
end
for r = 1, rowNum.third or rows do
        newRow(r)
end
p:saveStr('solid', tab.line[1][true], ' solid')
p.cornerDiv = mw.html.create'div':css{height = tab.line[1][true], ['borde
for c = 1, p.cols do
        col.c = c
        local bumps = bump
        if c > 1 then
                col.tot = col.tot + math.pow(2, p.tCols - c)
                if p.branch_upwards then
                        bumps = 0
                        rowNum[1]:tag'td':attr{rowspan = 4}
                else
                rowNum[1]:node(c < p.cols and
                        mw.clone(bumpBase):attr{rowspan = bump}
                        or p.no_column_head and p.template and
                                mw.html.create'td':wikitext(mw.getCurrent
                                        title = 'navbar-header',
                                        args = {'', p.templateFixedName}
                                })
                )
                end
        end
        col.top = m.num
        p.span = p.tCols > c and bump * 2 or p.branch_upwards or math.max
        col.show3rd = p['3rdplace'] and c == p.tCols and rowNum.third
        local colorFinal, bumpMid = p.color and c == p.tCols, p.span > 0
        for r = 1, col.show3rd or rows, 2 do
                m.r = r + bumps
                if col.show3rd or rowNum[m.r] and m.num <= col.tot then
                        if m.phase == 0 then
                                m.showBox = setmetatable({1, nodeArgs.tea
                                if nodeFunc:scanPattern(args, step) then
                                        nodeFunc.called = {}
                                        m.available = true
                                else
                                        m.available = nil
```

```
                        end
                end
                if skipMatch[m.num] then
                        if m.phase == 0 then
                                if nodeFunc.pattern then
                                        for x, y in ipairs(nodeFu
                                                if nodeFunc.skipA
                                                        nodeFunc
                                                end
                                        end
                                end
                                local canvas = nodeFunc.pattern a
                                rowNum[m.r + (canvas or 0)]:tag't
                        elseif m.phase == 2 then
                                if nodeFunc.pattern and (nodeFunc
                                        step = step + 1
                                end
                                m.num = m.num + 1
                                step = step + (p.omit_blanks and
                                bumps = bumps + (col.show3rd and
                        end
                elseif m.phase == 0 then
                        if nodeFunc.pattern then
                                for x, y in ipairs(nodeFunc.patte
                                        if nodeFunc[y] and nodeFu
                                                nodeFunc.called[y
                                        end
                                end
                                if m.available == false then
                                        m.showBox = nodeArgs.blan
                                        step = step + 1
                                end
                        end
                        if m.showBox[1] then
                                if col.show3rd then
                                        col.show3rd = (m.num - co
                                        if col.show3rd == 2 then
                                                if p.textThird:ma
                                                        p.textThi
                                                end
                                                if rowNum[rows +
                                                        rowNum[ro
                                                                t
                                                                c
                                                        }
                                                end
                                                if p.tCols == 1 t
                                                        bumps = p
                                                elseif p.branch_u
                                                        r = 7
                                                        bumps = p
                                                end
                                                m.r = r + bumps
                                                if p.textThird th
                                                        drawHead(
                                                        bumps = b
                                                        m.r = r +
                                                end
                                        end
                                end
                                dpBox(nodeFunc.pattern and nodeFu
                                if p.previewnumbers then
                                        rowNum[m.r].nodes[#rowNum
                                                :tag'div'
```

```
                                                        :css{
                                                                f
                                                                b
                                                                p
                                                                l
                                                        }
                                                        :wikitext
                                                        :attr{tit
                                        end
                                end
                                if p.colspan then
                                        m.nonEmpty = {}
                                        for s = step + 2, step + nodeArgs
                                                local i = {s, s + nodeArg
                                                if args[i[1]] or args[i[2
                                                        table.insert(m.no
                                                end
                                        end
                                        if p.bold and m.showBox[2] and m.
                                                m.bold = {
                                                        box = {},
                                                        clean = {}
                                                }
                                                local notSummed = not p.s
                                                for s, i in ipairs(m.nonE
                                                        m.bold.clean[s] =
                                                        m.bold.box[s] = m
                                                end
                                                if p.scoreSumBox and m.no
                                                        local i = {-step,
                                                        table.insert(m.no
                                                        args[i[1]], args[
                                                        m.bold.box[p.scor
                                                end
                                                getmetatable(boxStyle).__
                                                m.bold.win = m.bold.box[#
                                        else
                                                m.bold = infiniteEmpty
                                        end
                                end
                        else
                                if m.showBox[m.phase] then
                                        p.teamBoxCSS = colorFinal and
                                                {border = p.teamBoxNormal
                                                or p.teamBoxNormal
                                        local f = {phase = m.phase, bold
                                        teamBox(args[step + nodeArgs.team
                                        f[1] = 'center'
                                        if p.colspan then
                                                if m.nonEmpty[1] then
                                                        local loneSum
                                                        if #m.nonEmpty <
                                                                loneSum =
                                                                tab.r:att
                                                        end
                                                        for s, i in ipair
                                                                f.borderL
                                                                f.sumBox
                                                                f.bold =
                                                                teamBox(a
                                                        end
                                                else
                                                        for s = 1, p.scor
                                                                f.borderL
```

```
                                                                teamBox(r
                                                                        end
                                                                end
                                                        end
                                                end
                                                if m.phase == 2 then
                                                        col.show3rd = col.show3rd ~= 2 ar
                                                        if p.scoreWasher.demo and p.score
                                                                table.insert(m.bold.clear
                                                                return table.concat{
                                                                        'Score data for r
                                                                        mw.dumpObject{sc
                                                                        '<table>',
                                                                        tostring(sp.row),
                                                                        tostring(rowNum[r
                                                                        tostring(rowNum[r
                                                                        tostring(rowNum[r
                                                                }
                                                        end
                                                        if nodeFunc.orphan.num == m.num t
                                                                skipMatch[m.num] = 'orpha
                                                        end
                                                        step = step + m.showBox
                                                        m.num = m.num + 1
                                                        if bump > 0 and rowNum[m.r + 2] a
                                                                bumps = bumps + p.span
                                                                rowNum[m.r + 2]:node(bump
                                                        end
                                                        r = r + (col.show3rd or bump)
                                                end
                                        end
                                        m.phase = (m.phase + 1) % 3
                                end
                        end
                        if p.cols > c then--draw lines to next round
                                p.unit = bump + 3
                                bump = 3 * math.pow(2, c) - 3
                                bumps = p.branch_upwards and 4 or (p.unit + 1)
                                rowNum[1]
                                        :tag'td':attr{rowspan = bumps}
                                if not p.branch_upwards then
                                        rowNum[1]:tag'td'
                                                :attr{rowspan = (p.branch_upwards or bump
                                                :css(nodeFunc.bridge.lay[c](0) and
                                                        {['border-right'] = p.reuseStr.sc
                                                        or {}
                                                )
                                end
                                col.n = 0
                                for r = bumps + 1, rows, p.unit * 2 do
                                        tab.r = rowNum[r]:tag'td'
                                        local interval = ((r - bumps - 1) / (p.unit * 2))
                                        if interval % 2 == 0 then
                                                --col.t and col.t2 control whether lines
                                                col.t = col.t2 or skipMatch[col.tot + col
                                                col.n = col.n + 2
                                                col.t2 = skipMatch[col.tot + col.n / 2 +
                                                if col.t == 0 then
                                                        tab.r
                                                                :attr{rowspan = maxSpan(p
                                                                :css(skipMatch[col.tot +
                                                                        border = p.reuseS
                                                                        ['border-left'] =
                                                                })
```

```
                                        else
                                                tab.r
                                                        :attr{rowspan = maxSpan(p
                                                        :cssText(col.t == 2 and
                                                                p:saveStr('topRig
                                                                or col.t == 1 and
                                                                        p:saveStr
                                                                        or 'verti
                                                                )
                                                                or nil
                                                        )
                                                        :node(col.t == 1 and inte
                                                rowNum[r + (p.branch_upwards and
                                                        :attr{rowspan = maxSpan(p
                                                        :cssText(col.t == 1 and
                                                                p:saveStr('bttmRg
                                                                or col.t == 2 and
                                                                        p:saveStr
                                                                        or 'verti
                                                                )
                                                                or nil
                                                        )
                                                        :node(col.t == 2 and inte
                                        end
                                        col.t = {
                                                col.t < 3,
                                                rowNum[r + p.unit * 5] and col.t2
                                        }
                                        rowNum[r + (p.branch_upwards or p.unit)]:
                                                :attr{rowspan = maxSpan(p.unit *
                                                :css(interval == 0 and (col.t[1]
                                                        ['border-width'] = table.
                                                        ['border-style'] = 'solid
                                                } or {})
                                else
                                        tab.r
                                                :attr{rowspan = maxSpan(p.unit *
                                                :css(nodeFunc.bridge.lay[c](col.r
                                                        {['border-right'] = p.reu
                                                        or {}
                                                )
                                end
                        end
                end
        end
        local lock_height = (head_br.count or 0) + 1
        return args.scroll_height and
                mw.html.create'div'
                        :cssText'border-bottom:1px solid #eee;display:inline-bloc
                        :node(not (p.scroll_head_unlock or p.no_column_head) and
                                :css{
                                        overflow = 'hidden',
                                        height = lock_height * 1.4 + 1.6 .. 'em',
                                        ['border-bottom'] = 'inherit',
                                        ['margin-right'] = '17px'
                                }
                                :node(mw.clone(tab))
                        )
                        :tag'div'
                                :css{
                                        ['overflow-y'] = 'scroll',
                                        ['max-height'] = tonumber(args.scroll_hei
                                }
                                :node(not (p.scroll_head_unlock or p.no_column_he
```

```
                                        tab:css{['margin-top'] = math.floor(-10 *
                                        or tab
                                )
                        :done()
                or tab
end

--[[local standard = {
        'beta' = {
                bold_winner = 'high',
                omit_blanks = 'yes',
                auto_3rd = 'yes'
        }
}--]]
function p.main(frame, columns)
        local args = require'Module:Arguments'.getArgs(frame, {trim = false})
        args.columns = args.columns or columns
        return p._main(args)
end

function p.seed(frame)
        local parent = frame:getParent() or frame
        local function arg(k, alt)
                return parent.args[k] or frame.args[k] or alt
        end
        local padding, width = arg(2, p.teamBoxPadding()), arg(3, arg('widescore'
        padding = tonumber(padding) and tonumber(padding) .. 'px' or padding
        width = tonumber(width) and tonumber(width) .. 'px' or width
        return mw.html.create'div'
                :css{
                        margin = ('-1px %s -1px -%s'):format(padding, padding),
                        float = 'left',
                        ['background-color'] = p.bgColor.head,
                        border = '1px solid #aaa',
                        ['text-align'] = 'center',
                        width = width
                }
                :wikitext(arg(1, ' '))
end

return p
```

# Modul:RoundN/Doku

**Dies ist die Dokumentationsseite für Modul:RoundN**

**Inhaltsverzeichnis**

1 Usage ..... 22
2 Parameter List ..... 22
2.1 Example 1 ..... 23
2.2 Example 2 ..... 25
3 Node Functions ..... 27
4 Undocumented features ..... 28
4.1 Partial List of undocumented params ..... 28

## Usage

This is a module for meta templates such as Vorlage:Tl, Vorlage:Tl, etc. Though originally designed for sports, it can be used to present any tree.

Basic form:

```
{{#invoke:RoundN|main|columns = [number of columns (3 columns for Round8, 4 colu
```

Alternatively, the shorthand form `{{#invoke:RoundN|N16}}` (or any power of 2 between N2 and N512) is equivalent to Vorlage:Code

## Parameter List

- Vorlage:Red parameter names are required.
- *italicized* parameter names are required in some cases
- Vorlage:Blue parameter names involve new features not available prior to the release of this module

| Parameter name | Description |
|---|---|
| Vorlage:TOC tab | Number of columns/eliminations (3 columns for Round8, 4 columns for Round16, etc.)<br>**Note**<br>• For `columns` *less than 4* (i.e. Round2-Round8), the 3rd Place match box is hidden by default. For `columns` *greater or equal to 4*, the 3rd Place match box is visible by default. This reflects the behavior of the templates prior to this module's release. |

| Parameter name | Description |
|---|---|
| | Vorlage:TOC tab While required for invoking the main function (`{{#invoke:RoundN\|main\|columns=}}`), this module has meta functions in the form of 'N##' which can call main with the right Vorlage:Code for you. For example, you may replace `...\|main\|columns = 7...` with `...\|N128 ...`. Valid for N# where # is a power of 2. You must invoke this module directly to use this (vs. a template that already has a columns value). Only works up to N512. If say N1024 ever becomes necessary, call main directly and set Vorlage:Para.<br><br>PS: Though adding shorthands up to N ~70 trillion would be easy, it would make unnecessary overhead as these meta functions are generated eached time this module is called (granted generating such functions up to ~70 trillion is probably less expensive than making the table for columns = 3). |
| Vorlage:TOC tab | Unnamed parameters (i.e. a value not prefixed by `[param_name] =`) are read sequentially in groups of 5 such that:<br><br>**Example 1**<br><br>Vorlage:Demo Placing each group of 5 on a new line is optional, but does make it easier to read. Also, consider adding the comments such as `<!-- Date-Place/Team 1/Score 1/Team 2/Score 2 -->` on top and `<!-- Finals -->` above the first group of 5 in the finals round, etc. |
| Vorlage:TOC tab | Set the `style` parameter to add custom CSS to the table.<br><br>Modul Diskussion:RoundN/testcases/1 |
| Vorlage:TOC tab | For large tables, set Vorlage:Code to the desired height in pixels.<br><br>Modul Diskussion:RoundN/testcases/1<br><br>CSS units are also allowed (i.e. '20em', '30%', etc.). |

| Parameter name | Description |
|---|---|
| | **Note** This works by duplicating the entire table and then using CSS to lock the clone of the table to the top of the div. Conceivably, for extremely large tables, this can result in a significant amount of extra HTML code to download versus if Vorlage:Code is used. |
| Vorlage:TOC tab | If it is desirable to have the round heading scroll with the table (such as if a larger viewing area is desired), set Vorlage:Code to 'yes'<br><br>Modul Diskussion:RoundN/testcases/1 |
| Vorlage:TOC tab | If set, boxes for the #th match group will not be shown. Most often used for playoffs or when the number of teams playing in the first round is not a power of 2.<br><br>Modul Diskussion:RoundN/testcases/1 Vorlage:TOC tab: The shorthand `\|skipmatch = 1-2;4;6-7` will do the same thing as:<br><br>`\|skipmatch1=yes`<br>`\|skipmatch2=yes`<br>`\|skipmatch4=yes`<br>`\|skipmatch6=yes`<br>`\|skipmatch7=yes`<br><br>**Note:**<br><br>• Unlike in the original templates, this module does not require leading zeroes in this parameter, i.e. skipmatch001 is the same as skipmatch1 (though it may make your template code easier to read if lead with an appropriate number of zeroes).<br>• The 5 parameters that would have populated the skipped box will be ignored regardless of value unless `omit_blanks` is set to 'yes' (see below).<br>• Previously, skipmatch only worked in the first round. This limitation no longer applies. (See Module talk:RoundN/testcases/3) |
| Vorlage:TOC tab | |

| Parameter name | Description |
|---|---|
| | If `omit_blanks` is set to yes, then all parameters that would have been skipped will instead be shifted to the next non-skipped box. (This is turned off by default because most templates made before the release of this module were required to use empty parameters as placeholders.)<br><br>Modul Diskussion:RoundN/testcases/1 |
| Vorlage:TOC tab | The Vorlage:Code parameter accepts either Vorlage:Code or Vorlage:Code, which will automatically bold the text of the participant with the *higher* or *lower* score, respectively. In other words, set this to 'low' if the lower score wins and 'high' if the high score wins.<br><br>**Example 2**<br><br>Modul Diskussion:RoundN/testcases/2 **Note:**<br><br>• If entering a score that includes non-numbersVorlage:--such as `3 (6)`, the Semi Final score for team C in the above exampleVorlage:--the module will first remove all non-digit characters and concatenate the rest. For example, `3 (5)` and `3 (6)` would be converted to `35` and `36`, respectively, before being compared. This should be valid for most cases, however, you may override using the `manualboldmatch##` parameter.<br>• If the scores are tied or contain no numbers, then neither will be bolded, however, you may still manually bold them with wikimarkup.<br>• This does not remove any formatting already present. |
| Vorlage:TOC tab | Modul Diskussion:RoundN/testcases/2<br><br>Vorlage:TOC tab The form `manualboldmatch = 1-3;6;9-12` is also available. |
| Vorlage:TOC tab | Set `\|previewnumbers = yes` to show numbers next to each match group (useful for Vorlage:Code and Vorlage:Code) when viewing on the template page. |

| Parameter name | Description |
|---|---|
| | Note that these numbers will not appear in article space. |
| Vorlage:TOC tab | Use `RD#`, replacing # with the desired column such that 1 is the leftmost round and X is the rightmost when `columns = X`. For example:<br><br>Vorlage:Demo **Note** RD[N+1] = Third Place, and will perform the job of the `Consol` parameter if the latter is omitted, i.e. RD[N+1] is ignored if Consol is true. Also, this alternate name for Consol was not available prior to the release of this module (and is provided because the module's programmer thought 'Consol' was unintuitive). |
| Vorlage:TOC tab | By default, `\|3rdplace=` is set to 'yes' when `columns` is greater than 3 and 'no' otherwise. Override as desired. (See `Consol` if you wish to rename this heading)<br><br>Vorlage:Demo |
| Vorlage:TOC tab | Set `Consol=name` to change the 'Third Place' label to 'name'. You may also use the form RD# where # = columns + 1.<br><br>Vorlage:Demo |
| Vorlage:TOC tab | Add `\|color=yes`<br><br>Final<br>7<br>Gold medalist 3<br>Silver medalist 2<br><br>Third place<br>8<br>Bronze medalist 1<br>0 |
| Vorlage:TOC tab | Set `team-width` to the desired width in pixels. (Default is 170) |
| Vorlage:TOC tab | Set `score-width` to the desired width in pixels. |

| Parameter name | Description |
|---|---|
| | (Default is 30) |
| Vorlage:TOC tab | Setting `\|widescore=yes` is basically equal to `\|score-width=40`. Provided for compatibility. Ignored if `score-width` is set. |
| Vorlage:TOC tab | Set `score-boxes` to the desired number of score boxes per match. (Default is 1). The number can be followed by `+ sum`, which will add one more score box with the sum of all the others. For examples, see test case 5 and test case 6. |
| Vorlage:TOC tab | Set `\|template=yes` if used to create a template for a specific game (add V.T.E. link using Vorlage:Tl). |
| Vorlage:TOC tab | Set `\|flex_tree=yes` to make the brackets more compact. That is, to have less space between matches of the same round. |

## Node Functions

Vorlage:Ombox

For greater customization, node functions may be added to the parameter usually used for providing match information such as dates and location. Simply insert `node_function{`*`function name`*`}` in the appropriate location. A demonstration of most of the node functions can be found at RoundN/testcases/4.

- **orphan** - Current node is disconnected from all other nodes (no lines will be drawn). One practical use for this may be when the winners of the previous round advance to a different tournament instead of playing each other but the losers still play a consolation match for 3rd place, as per this discussion.

For the next three node functions, the parameters usually used for team names and scores should be omitted if these node functions are used.

- **line** - Current node is omitted and replaced with a horizontal line. Text may be displayed above this line via `node_function{line(`*`text`*`)}` (at some point, the preferred format would be `node_function{line}`*`text`* to match the form of the canvas function though backwards compatibility would probably be maintained). If curly brackets are desired in the text, make sure to escape them with `\`.
- **bridge** - Current node is omitted and replaced with a vertical line.
- **canvas** - Current node is replaced with whatever you want via `node_function{canvas}` *`anything`*

- **heading** - Not yet implemented. Planned node function with the form `node_function {heading(*name*)}*date/location*`. Makes a round name heading like for the Consol parameter, but may be placed anywhere, as per the "Elimination Rounds" of RoundN/testcases/6 (which currently renders the planned output of this function without the functions).

## Undocumented features

Alas User:Codehydro seriously overbuilt this module and never found the time to document even half the features available. Check out the following examples which may contain some advanced features: Spezial:PrefixIndex/Module talk:RoundN/testcases

## Partial List of undocumented params

- no_column_head
- short_brackets
- branch_upwards

Note that some of these features may not have been documented due to incomplete implementation.