

Modul:Unsubst/Doku

Dies ist die Dokumentationsseite für Modul:Unsubst

Helper module to facilitate a substituted template transform into a template transclusion.

Maintenance templates, such as Vorlage:TI or Vorlage:TI, should never be substituted. A trick to avoid that is to make a template substitute to its transcluded form.

Infoboxes should use Module:Unsubst-infobox, as should any other templates with parameters listed in block format by default.

Usage

To turn a template into a self-substituting template, wrap the existing template code with:

```
{{SAFESUBST:<noinclude />#invoke:Unsubst||$B=
 [ ... existing template code ... ]
}}
```

The wikitext to display when not subst'd must be given as "\$B". All other parameters passed to the #invoke will be copied to the generated template invocation as default values. If the value of any of these default parameters is __DATE__, that value in the generated template invocation will be the current month and year.

Some templates have a Vorlage:Tag but no matching Vorlage:Tag at the end of the template. In such cases the missing Vorlage:Tag must be added before the ending Vorlage:)).

Advanced

```
{{SAFESUBST:<noinclude />#invoke:Unsubst||$params=[ parameters ]|$aliases=[ alias
 [ ... existing template code ... ]
}}
```

Due to Lua limitations, parameters are normally ordered randomly when the template is substituted. Vorlage:Para can be used in #invoke:Unsubst to list template parameters in order, comma-separated (e.g. egg, bacon, sausage, cheese, spam). Numbered parameters should be before others in the list. Any remaining parameters are tacked onto the end of the generated invocation.



Parameter aliases can be listed in **Vorlage:Para** (and shouldn't be listed in **Vorlage:Para**), and will be replaced automatically. Each alias and its replacement should be formatted as `alias>replacement`, and each of those pairs should be comma-separated (e.g. `œuf>egg`, `melt>cheese`). Note that this parameter can function with or without **Vorlage:Para**.

Parameter **Vorlage:Para** can be used to modify other facets of the module's behaviour; entries are comma-separated. Valid flags are `override` (allows parameters in the `#invoke:` to take precedence over parameters in the original template invocation); `keep-whitespace` (prevents whitespace from being trimmed from unnamed parameters); and `remove-empty` (removes empty parameters).

These parameters can be manipulated using parser functions to provide more complicated options (note that in the parameters any parser function, or template or module invocation, should also have `SAFESUBST:<noinclude />`).

Parameter **Vorlage:Para** will override the subst'd templates name with the template name assigned to this parameter.

Example

Consider a template `Template:Example` containing the following code:

```
{{SAFESUBST:<noinclude />#invoke:Unsubst||foo=bar |date=__DATE__ |$B=
 [ ... Template code goes here ... ]
}}
```

Original	Result
Vorlage:Tlsc	Vorlage:Tlc
Vorlage:Tlsc	Vorlage:Tlc
Vorlage:Tlsc	Vorlage:Tlc
Vorlage:Tlsc	Vorlage:Tlc