



# Inhaltsverzeichnis

---

1. Modul:Ustring .....	2
2. Modul:Ustring/Doku .....	6

## Modul:Ustring

This module directly imports all functions from the [Vorlage:Luaref](#) library. Documentation for each function can be found there.

The module takes an indefinite number of arguments. Arguments given as [Vorlage:Para](#), [Vorlage:Para](#), etc, are read first, and are used as strings. All remaining numerical arguments are coerced to number type if possible, and remain strings if not. If you wish for a numerical (i.e. unnamed or "[Vorlage:Para](#)", "[Vorlage:Para](#)") to remain a string, you can simply escape it by inserting `\` at the beginning of the string.

Note that MediaWiki will always trim whitespace from named arguments; to give arguments with surrounding whitespace you must use unnamed parameters starting with `\`.

### How to pass inconvenient strings

To pass this...	Write this	Explanation
" 0123 "	<a href="#">Vorlage:Para</a>	To get surrounding whitespace must use unnamed, but must precede with <code>\</code> to indicate that it isn't a number.
"0123"	<a href="#">Vorlage:Para</a>	If you don't need to preserve whitespace use <a href="#">Vorlage:Para</a> etc.
"0123"	<a href="#">Vorlage:Para</a>	If you don't need to preserve whitespace explicitly use <a href="#">Vorlage:Para</a> etc.
In another template, to pass its parameter <code>{{{1}}}</code> , preserving whitespace	<a href="#">Vorlage:Para</a>	Must provide the <code>\</code> with unknown string input.
In another template, to pass its parameter <code>{{{1}}}</code> , stripping whitespace	<a href="#">Vorlage:Para</a>	
In another template, to pass its parameter <code>{{{1}}}</code> , stripping whitespace	<a href="#">Vorlage:Para</a>	

You can also wrap results in tags. All other unused arguments will be passed to [Vorlage:Luaref](#)

Inhaltsverzeichnis	
1 Usage .....	3
1.1 Example using <code>mw.ustring.sub</code> .....	3
1.2 Example using <code>mw.ustring.gsub</code> .....	3

1.3 Example using mw.ustring.char .....	3
1.4 Example using mw.ustring.match .....	3
1.5 Example using tag arguments .....	4
2 Errors .....	4
3 See also .....	5

## Usage

---

{{#invoke:Ustring|*function\_name*|arg1|arg2|...}} is equivalent to [Vorlage:Luaref](#)

### Example using mw.ustring.sub

---

```
{{#invoke:Ustring|sub|s1=abcde|2|4}}
```

produces:

bcd

### Example using mw.ustring.gsub

---

```
{{#invoke:Ustring|gsub|s1=1234|23|}}
```

produces:

14

### Example using mw.ustring.char

---

```
&#amp;#{{#invoke:ustring|char|49|48|59}}
```

produces:

&#10;

### Example using mw.ustring.match

---

```
{{#invoke:Ustring|match|s1=abcde|s2=(c%w)}}
```

produces:

cd

Note: Only the first match is returned. Additional returns are omitted because mw.ustring.gsub's second return value is generally undesirable.



## Example using tag arguments

```

{{#invoke:Ustring|match
|s1={{Module:Ustring}}|%s%s%sif%not%s[^%s]+%sthen.+%
<!---enter an actual newline character to match '\n'-->%s%s%send
|tag=syntaxhighlight|lang=lua}}

```

produces:

```

if not fargs.tag then
    return (what(unpack(args))) -- Out
end
local tagargs = {}
for x, y in pairs(fargs) do
    if not fargsused[x] then tagargs[x] = y end
end

```

Note that:

```

<syntaxhighlight lang="lua">{{#invoke:Ustring|match
|s1={{Module:Ustring}}|%s%s%sif%not%s[^%s]+%sthen.+%
<!---enter an actual newline character to match '\n'-->%s%s%send}}</syntaxhighlight

```

produces:

```

{{#invoke:Ustring|match
|s1={{Module:Ustring}}|%s%s%sif%not%s[^%s]+%sthen.+%
<!---enter an actual newline character to match '\n'-->%s%s%send}}

```

## Errors

Errors from accessing [Vorlage:Luaref](#) should be maintained, e.g.:

```

{{#invoke:Ustring|xyzyzy}}

```

should produce:

[Vorlage:Script error](#)

and

```

{{#invoke:Ustring|maxPatternLength}}

```

should produce:

[Vorlage:Script error](#)

## See also

### Vorlage:String handling templates

```
require('Module:No globals')
return setmetatable({}, {
    __index = function(t, k)
        local what = mw.usttring[k]
        if type(what) ~= "function" then
            return what
        end
        return function(frame)
            local fargs = frame.args
            local fargsused = { tag = true }
            local args = {}
            local str_i = 1
            while fargs['s' .. str_i] do
                fargsused['s' .. str_i] = true
                args[str_i] = fargs['s' .. str_i]
                str_i = str_i + 1
            end
            for i, v in ipairs(fargs) do
                fargsused[i] = true
                args[i + str_i - 1] = tonumber(v) or v:gsub("^\\")
            end
            if not fargs.tag then
                return (what(unpack(args))) -- Out
            end
            local tagargs = {}
            for x, y in pairs(fargs) do
                if not fargsused[x] then tagargs[x] = y end
            end
            return frame:extensionTag{name = fargs.tag, content = wha
        end
    end
end
})
```

## Modul:Ustring/Doku

### Dies ist die Dokumentationsseite für Modul:Ustring

This module directly imports all functions from the [Vorlage:Luaref](#) library. Documentation for each function can be found there.

The module takes an indefinite number of arguments. Arguments given as [Vorlage:Para](#), [Vorlage:Para](#), etc, are read first, and are used as strings. All remaining numerical arguments are coerced to number type if possible, and remain strings if not. If you wish for a numerical (i.e. unnamed or "[Vorlage:Para](#)", "[Vorlage:Para](#)") to remain a string, you can simply escape it by inserting `\` at the beginning of the string.

Note that MediaWiki will always trim whitespace from named arguments; to give arguments with surrounding whitespace you must use unnamed parameters starting with `\`.

#### How to pass inconvenient strings

To pass this...	Write this	Explanation
" 0123 "	<a href="#">Vorlage:Para</a>	To get surrounding whitespace must use unnamed, but must precede with <code>\</code> to indicate that it isn't a number.
"0123"	<a href="#">Vorlage:Para</a>	If you don't need to preserve whitespace use <a href="#">Vorlage:Para</a> etc.
"0123"	<a href="#">Vorlage:Para</a>	If you don't need to preserve whitespace explicitly use <a href="#">Vorlage:Para</a> etc.
In another template, to pass its parameter <code>{{{1}}}</code> , preserving whitespace	<a href="#">Vorlage:Para</a>	Must provide the <code>\</code> with unknown string input.
In another template, to pass its parameter <code>{{{1}}}</code> , stripping whitespace	<a href="#">Vorlage:Para</a>	
In another template, to pass its parameter <code>{{{1}}}</code> , stripping whitespace	<a href="#">Vorlage:Para</a>	

You can also wrap results in tags. All other unused arguments will be passed to [Vorlage:Luaref](#)

## Inhaltsverzeichnis

1 Usage .....	7
1.1 Example using mw.ustring.sub .....	7
1.2 Example using mw.ustring.gsub .....	7
1.3 Example using mw.ustring.char .....	7
1.4 Example using mw.ustring.match .....	7
1.5 Example using tag arguments .....	8
2 Errors .....	8
3 See also .....	8

## Usage

`{{#invoke:Ustring|function_name|arg1|arg2|...}}` is equivalent to [Vorlage:Luaref](#)

### Example using mw.ustring.sub

```
{{#invoke:Ustring|sub|s1=abcde|2|4}}
```

produces:

bcd

### Example using mw.ustring.gsub

```
{{#invoke:Ustring|gsub|s1=1234|23|}}
```

produces:

14

### Example using mw.ustring.char

```
&#amp;#{{#invoke:ustring|char|49|48|59}}
```

produces:

&#10;

### Example using mw.ustring.match

```
{{#invoke:Ustring|match|s1=abcde|s2=(c%w)}}
```

produces:

cd

Note: Only the first match is returned. Additional returns are omitted because mw.ustring.gsub's second return value is generally undesirable.



## Example using tag arguments

```

{{#invoke:Ustring|match
|s1={{Module:Ustring}}|%s%%sif%not%[^%s]+%sthen.+%
<!---enter an actual newline character to match '\n'-->%s%%s%send
|tag=syntaxhighlight|lang=lua}}

```

produces:

```

if not fargs.tag then
    return (what(unpack(args))) -- Out
end
local tagargs = {}
for x, y in pairs(fargs) do
    if not fargsused[x] then tagargs[x] = y end
end

```

Note that:

```

<syntaxhighlight lang="lua">{{#invoke:Ustring|match
|s1={{Module:Ustring}}|%s%%sif%not%[^%s]+%sthen.+%
<!---enter an actual newline character to match '\n'-->%s%%s%send}}</syntaxhighlight

```

produces:

```

{{#invoke:Ustring|match
|s1={{Module:Ustring}}|%s%%sif%not%[^%s]+%sthen.+%
<!---enter an actual newline character to match '\n'-->%s%%s%send}}

```

## Errors

Errors from accessing [Vorlage:Luaref](#) should be maintained, e.g.:

```

{{#invoke:Ustring|xyzyzy}}

```

should produce:

[Vorlage:Script error](#)

and

```

{{#invoke:Ustring|maxPatternLength}}

```

should produce:

[Vorlage:Script error](#)

## See also

[Vorlage:String handling templates](#)